


KABLOLARA GÖRE REKOR SEÇİM CETVELİ					
ANMA GERİLİMİ : 0.6/1 kV					
EN YÜKSEK İLETKEN SICAKLIĞI :				70°C	
SN.	ANMA KESİTLİ mm <sup>2</sup>	DIŞTAN DIŞ ÇAP mm	KABLO REKORU	BÜKÜM ÇAPI cm	DİRENÇ Ω/km
1	1x1.5	8	PG 13.5	11	11.9
2	1x2.5	8.4	PG 13.5	11	7.14
3	1x4	8.9	PG 13.5	12	4.47
4	1x6	9.4	PG 13.5	13	2.97
5	1x10	10.7	PG 13.5	14	1.79
6	1x16	11.7	PG 16	15	1.12
7	1x25	12.9	PG 16	18	0.712
8	1x35	14.1	PG 21	20	0.514
9	1x50	15.6	PG 21	23	0.379
10	1x70	17.2	PG 29	26	0.262
11	1x95	19.4	PG 29	29	0.189
12	1x120	21.4	PG 29	30	0.150
13	1x150	23	PG 29	33	0.122
14	1x185	25.7	PG 29	36	0.0972
15	1x240	29	PG 36	44	0.0740
16	1x300	32	PG 36	48	0.0590
17	2x1.5	11	PG 13.5	14	12.1
18	2x2.5	13	PG 16	16	7.28
19	2x4	14	PG 16	17	4.56
20	2x6	15	PG 21	18	3.03
21	2x10	17	PG 21	21	1.83
22	3x1.5	12	PG 16	15	12.1
23	3x2.5	13	PG 16	16	7.28
24	3x4	15	PG 21	19	4.56
25	3x6	16	PG 21	20	2.03
26	3x10	17	PG 21	21	1.83
27	4x1.5	13	PG 16	16	12.1
28	4x2.5	14	PG 16	17	7.28
29	4x4	16	PG 21	19	4.56
30	4x6	17	PG 21	21	3.03
31	4x10	20	PG 29	23	1.83
32	4x16	23	PG 29	27	1.15
33	3x25/16	27	PG 36	33	0.7270
34	3x35/25	30	PG 36	36	0.524
35	3x50/25	36	PG 42 (Pirinç)	44	0.387
36	3x70/35	40	PG 42 (Pirinç)	49	0.268
37	3x95/50	45	PG 48 (Pirinç)	55	0.193
38	3x120/70	50	PG 55 (Pirinç)	61	0.153
39	3x150/70	52	PG 55 (Pirinç)	69	0.124
40	3x185/95	59	PG 60 (Pirinç)	77	0.0991
41	3x240/120	66	PG 70 (Pirinç)	82	0.574
42	3x300/150	73		92	0.0601

## KABLO REKORU DELİKLERİ



## DELİK ÇAPI ( mm )

REKOR ANMA ADI	YAĞ BOYA	TOZ BOYA
PG 9	16	17
PG 11	19	20
PG 13.5	21	22
PG 16	22,5	23,5
PG 21	29	30
PG 29	37	39
PG 36	47	49
PG 42	54	56
PG 48	60	56
PG 55	63	65
PG 60	66	68